


Spiral-Wound Gasket Product Range


Description:

3S SWG gaskets are wound with a “V” section profiled metal strip along with a soft filler material. The “V” section metal strip ensures the gasket has excellent compressibility and recovery under various applications. The soft filler material ensures sealability against the flange face, offering optimum performance. 3S SWG can be produced in a wide range of sizes, thickness and material combinations to suit the application.


Style:



Style S - SI is a spiral wound gasket that is fabricated by utilizing the metal wire along with soft non-metallic filler. Suitable for tongue and groove, male and female, or grooved to flat face flange assemblies, also available with pass bars




Style GS are comprised of the metal wire with designated filler incorporating the use of a solid metal outer ring. The outer guide ring promotes the correct centering of the gasket in a standard flange, offers radial support for the outer portion of the spiral wound, and acts as a compression gauge to prevent over compression of the spiral wound.



Style GSI are the same as our Style GS with a addition of an inner ring. Like the outer ring, the inner ring serves multiple functions including: radial support for the inner portion of the spiral wound, prevents inward buckling and helps to provide uniform gasket stress

FIRE SAFE APPROVED
ACCORDING TO
API 6FB (GRAPHITE FACING)



Maximum Temperature (Filler)	
3S Inhibited Graphite	850°F (454°C)
APX2® Graphite	975°F (524°C)
PTFE	500°F (260°C)
Mica	1800°F (982°C)
Mica/APX2®/Mica (HTG)	Min -238°F (-150°C) Max 1500°F (815°C)
Ceramic	2000°F (1093°C)
Maximum Temperature (Alloys)	
304 / 304L SS	1400°F (760°C)
316 SS	1400°F (760°C)
316L SS	1400°F (760°C)
321 SS	1500°F (815°C)
347 SS	1500°F (815°C)
Monel	1500°F (815°C)
Inconel 600	2000°F (1093°C)
Carbon Steel	900°F (482°C)